
# www.forteparke.com



FORTE TRU SPC, was created to provide distributors & consumers with premium quality European SPC floors. Our dedicated commitment to offering our clients, the absolute best overall; product image, value, quality, design visuals, packaging, and efficient service is what sets our company apart.



## ENDURANCE TECH CORE

quality and completely safe formula which consists of 70% Natural Stone, Virgin PVC, as well as the highest-grade polymers and minerals fused together under heat & high pressure using special tech Extruders. Our Core provides next level performance above and beyond competing products.

### PRODUCTION

State of the art, 300,000 sqft Factory located in Bursa Turkey. Equipped with fully automated, high output production lines and a talented technical team, capable of producing large volumes of impressive products.

### PREMIUM QUALITY EUROPEAN PRODUCTS

Provide your clients with the prestige of European SPC Floors. Our products present a luxury & desirable image and are also perceived as superior quality. We also back this up, with our unwavering commitment to using only top quality & locally sourced raw materials, which positions our products in a higher class category. As a company we are dedicated to offering nothing less then the "best overall value". With these principals, we provide several important advantages while still being competitive with Asian imports.

Large Inventory is maintained in our 130,000 sqft Toronto area distribution centres; ready to reach your facility within days. No need to wait 2 - 3 months for products to arrive from Asia. Have the comfort of knowing our products are only days away from your facility; so you can focus on fulfilling your clients needs without delays. Additionally, keeping less inventory & ordering more frequently allows our clients to significantly free up finances, reduce overhead costs, and minimize risk. As a team, we places a high emphasis on providing exceptional service which extends to handling all your logistics to your door. Our mission is to simplify your business.

### NATURE INSPIRED COLORS & DESIGNS

Our in house design staff works meticulously to create impressive product colors, designs and surface textures that emulate real wood species. Our selections are sure to add elegance and beauty to any space. The boxes & packaging we provide are presentable, informative

## **COMPANY BACKGROUND**

Although our factories are considerably new, our experience in manufacturing dates back to 2005. With our roots in natural stone production, we have been quarrying and processing Marble and Travertine for almost 15 years. Since 2005, we have produced over 70 million square feet of tiles, mosaics and wall cladding in our factories in Turkey for the North American market. Now we have expanded our production into SPC. Our investments in Georgia, USA and in Bursa, Turkey allows us to produce a total of 50+ million square feet of SPC annually. With a combined area of 380,000 sqft in manufacturing facilities, equipped with the latest automated machinery, FORTE TRU & ROKPLANK are becoming key suppliers of SPC flooring to the North American market.



Stain Resistant

HEALTHY FLOORING CHOICE

Our uncompromising core values are to produce and supply superb quality products that promotes a healthy environment in any setting. Our SPC Rigid Core Floors have been tested by Intertek Sustainability and achieved Clean Air Gold Certification. In addition, the raw materials we use in production are also tested regularly by third party sources to ensure they meet and exceed the highest quality and health standards.

Feel comfortable knowing that our products:

- -Are Completely safe to be used in various indoor applications.
- -Meet the most stringent air quality emissions criteria.
- -Do not contain harmful materials such as benzene, formaldehyde, phthalate, or heavy metals.
- -Are Antibacterial; impeding the growth of bacteria, fungi and mold.
- -Are ethically produced with recycling systems that produce zero manufacturing wa





PLANK SIZE: 7.13" X 48" INCHES | MICRO BEVELED EDGES <u>CORE</u>: SPC (STONE POLYMER COMPOSITE) <u>THICKNESS</u>: 5MM (WITH 1.0MM HIGH DENSITY PRE-ATTACHED UNDERPAD) PROTECTION: ULTIMATE SHIELD SCRATCH, STAIN AND WEAR RESISTANT DOUBLE UV COATING <u>WEAR LAYER</u>: 22MIL (0.55MM) | 20MIL (0.50MM) <u>VISUALS</u>: ULTRA HD, NATURE INSPIRED REALISTIC WOOD <u>SURFACE</u>: WOOD GRAIN EMBOSSED, IMPRESSIVE TEXTURES <u>CARTON</u>: 10 PIECES, 23.8 SQFT / 55 CARTONS PER PALLET, 1309 SQFT <u>WEIGHTS</u>: 42 LBS PER CARTON / 2300 LBS PER PALLET INSTALLATION: 14F LOCKING SYSTEM <u>RESIDENTIAL WARRANTY</u>: 25 YEAR LIMITED <u>LIGHT COMMERCIAL WARRANTY</u>: 10 YEAR LIMITED



ULTIMATE SHIELD TECHNOLOGY: Sets a new industry benchmark in surface protection. This Special UV Coating Technology provides superb performance in Scratch, Stain and Wear Resistance (10x Stronger Resistance then regular UV) It is sourced from an American company and found on all FORTE TRU Products

## COMPOSITION

ULTIMATE SHIELD SCRATCH RESISTANT UV COATING 10X STRONGER AT RESISTING SCRATCHES, STAINS AND ABRASIVES THEN REGULAR UV

20 MIL WEAR LAYER PROTECTS THE HD FILM

HD PRINT FILM WITH WIDE VARIATION

DROP-LOCK SYSTEM

STONE POLYMER COMPOSITE (SPC) CORE 100% WATERPROOF CORE 14F DROP LOCK SYSTEM 2000 KGS/M3 DENSITY 70% LIMESTONE

HIGH DENSITY IXPE PAD UNDERLAYMENT SUPERIOR TO EVA UNDERLAYEMNT ADVANCED SOUND REDUCTION PROVIDE EXTRA COMFORT







FORTE TRU

## **QUALITY CONTROL PROCESS** PHASES OF PRODUCTION

### UNDERPAD **EXTRUSION CUTTING &** ULTIMATE ADHESION PACKAGING LINES SHIELD UV PROFILE LINES LINES

PRIOR TO RAW FINISHING DELIVERY MATERIALS MIXING STEPS TAKEN STEPS TAKEN STEPS TAKEN STEPS TAKEN **STEPS TAKEN** -Plant Supervisor -Engineers and Technical Team **Technical Team closely** -Final Quality Control is -Employees at this station performed on products. Boxes makes sure all raw closely monitor: Monitors proper monitor proper adhesion of are randomly pulled / checked Mixing Ratios, precise & strong materials recieved operation of cutting pads to planks, as well as size meets our high quality lamination of multiple layers and and profile line: each hour to insure they meet and cutting quality. A third criteria. proper operation of all systems. Every 15 minutes inspection for plank defects our stringent requirements. -Periodic testing - Physical inspections of extruded Several products are and overall quality takes -Warehoue & logistics team labels all boxes / pallets and performed products including quality, strength, pulled, carefully place. inspects packaging quality. sizing, emboss and gloss levels -Automatic Mixing inspected with tools - Automated high speed System provides exact - Monitor use of Ultimate Shield and installed together -All orders get staged and final packaging line insures precise sensetive Double UV coating application to check for any defects and quick boxing & palletizing check performed for order measurements of raw system. Inspect all boards for even in sizing or locking of all products. Completed quantities and possible materials required in and proper coating. Additional mechanism. Blades and pallets put into inventory. damages prior to and after loading. Products leave facilty production overal quality check performed on profile inspected each shift for 100% accuracy. all boards






## **PREMIUM QUALITY FLOORS**




## WHY IS FORTE TRU SPC THE BEST FLOORING CHOICE ?

Resistant | Impact Resistant | Lifetime Residential Warranty | Quick & Easy to Install | Patented click locking system | Easy to Maintain | Scratch Resistant | Ultra HD Stunningly Beautiful Wood Visuals | Natural wood feel surface texture | Healthy Flooring choice with no formaldehyde & no phalates & no heavy metals & no benzene & no plasticizes | Intertek Clean Air Certified Flooring; which meets stringent indoor air quality emissions criteria | Made from 70% Natural Stone & 30% Virgin PVC | Very affordable product and install cost | Worry & Stress free maintenance | Installs right over most hard & flat floors | Suitable with underfloor heating | Conforms to room temperature | Fire Resistant | Wear resistant | Safe, slip resistant surface | Sound Absorbing, built in high density underpad | Antibacterial | Premium Quality Products - which meet and exceed ISO & CE & ASTM standards | Attractive & Informative Packaging | Ultimate Shield Surface Coating; which provides industry leading and superb scratch, stain and wear resistance









0



Pacific 3





2614-1












2639-5


















Annue 1

29045-6





Silecto 2

29052-5




























1.4.1

and the set of
















29149-7















29150-1





## FORTE TRU RIGID CORE

EUROPEAN PREMIUM SPC FLOORS

			DIMENSIONS
Thickne	955		$5.00 \text{ mm} \cdot t_{max} - t_{min} \le 0.50 \text{ mm}$
Length		$1219.2 \text{ mm} \cdot I_{max} - I_{min} \le 0.50 \text{ mm}$	
Width		$181.1 \pm 0.10 \text{ mm} \cdot \text{W}_{\text{max}} - \text{W}_{\text{min}} \le 0.20 \text{ mm}$	
width			
Squarou	2055	EN 16511	$\leq 0.20 \text{ mm}$
Squareness Straightness		EN 16511	≤ 0.20 mm / m
Flatness Crosswise		EN 16511	$\leq 0.30 \text{ mm/ m}$ Concave: $\leq 0.15\% \cdot \text{convex}$ : $\leq 0.20\%$
Flatness Lengthwise		EN 16511	$Concave: \leq 0.15\% \cdot convex: \leq 0.20\%$ $Concave: \leq 0.50\% \cdot convex: \leq 1.00\%$
		EN 10511	$Concave: \leq 0.50\% \cdot convex: \leq 1.00\%$
Openings between Elements		EN 16511	Average: $\leq 0.15 \text{ mm} \cdot \text{max}$ : $\leq 0.20 \text{ mm}$
Height Difference between Elements		EN 16511	Average: $\leq$ 0.10 mm $\cdot$ max: $\leq$ 0.15 mm
		10	TEST
Abrasion Resistance Method B		EN 16511	$\geq$ 3000 cycles
Impact Resistance		EN 16511	≥ 1200 mm
Micro Scratch Resistance		EN 16511	$\leq$ MSR-A1
Stain Resistance	Group 1 & 2	EN 16511	Grade 5
	Group 3	EN 16511	Grade 4
Castor Chair Test		ISO 4918	No change in appearance after 25.000 cycles
Effect of Furniture Leg		EN 16511	No visible damage
Thickness Swelling		EN 16511	No swelling
<b>Residual Indentation</b>		EN 16511	≤ 0.20mm
Locking Strength		EN 16511	$f_{10,2} \ge 1 \text{ kN/m}$ (length); $f_{s0,2} \ge 1.5 \text{ kN/m}$ (width)
<b>Dimensional Stability</b>		EN 16511	≤ 0.25 %
			ENVIRONMENT
Emission of Formaldehyde		CDPH	PASS
			PHYSICAL BEHAVIOR
Fire Behaviour		EN 13501-1	Bfl-s1
Slide Resistance		EN 13893	DS
Thermal Resistance		EN 12667	0.01 (m²K)/W
Electrostatic Behaviour		EN 1815	Antistatic Floor Covering
		SOL	JND ABSORPTION QUALITIES
Calculated Impact		ASTM	110.00
	1. <b>*</b> • • •	E492-09	IIC 62
Insulation	n Class	L492-09	
Calculated		ASTM	STC 60

The data sheet is updated regularly to meet new technological standards. This version replaces all previous versions as well as those which are undated.

SPC RIGID CORE Flooring of floating installation, Level of use according to EN 16511: Class 32 FOR FLOORING TO BE USED IN LIVING AREAS AND COMMERCIAL PREMISES



Türkiye Distribütörü FORTE PARKE TASARIM ve ZEMİN ÜRÜNLERİ TİC. LTD. ŞTİ.

www.forteparke.com